


Product information



HEL copper sealing rings, round cord

Art.Nr.: CCW-Oring



Copper sealing rings as round cord (O-ring), for various applications

SPECIAL ARTICLE, only on request and procurement!

These special sealing rings are manufactured exclusively according to drawing and dimensions!

Product information



Example of copper O-rings already

- 274.40 x 4.80 mm
- 290.00 x 4.80 mm
- 348.40 x 3.20 mm
- 367.00 x 4.80 mm
- 384.24 x 3.20 mm
- 411.00 x 4.80 mm

Tighten brake lines, banjo bolts and connections!

Note Tightening torque for:

- Stainless steel fitting and stainless steel banjo bolts Min. 20 Nm - Max. 33 Nm.
- Stainless steel fitting and aluminum banjo bolt Min. 18 Nm - Max. 21 Nm.
- Aluminum fitting and stainless steel banjo bolt Min. 18 Nm - Max. 21 Nm.
- Aluminum fitting and aluminum banjo bolt Min. 18 Nm - Max. 21 Nm.

The vehicle manufacturer's tightening values must not be exceeded!

Braided steel brake lines and kits from HEL Performance:

HEL-Performance® brake line kit, including banjo bolts** and accessories**

- No expansion of the lines at high temperatures
- eliminates the spongy feeling on the brake lever
- direct and precise braking point
- Teflon inner core with stainless steel sheathing
- only stainless steel connections
- Lower maintenance costs for the brake system
- Motorsport proven technology

* For availability and delivery with ABE or parts certificate, please refer to the latest version of our ABE, which you can download here as a PDF file:

www.helperformance.com/certification

The ABE is updated on an ongoing basis. If your vehicle is not or not yet included, please contact us directly.

(** is included, if required)